

## Model : AN-AD9808T-M

### Feature :



- Adope the standard main profile H.264 Compression
- Support full real-time encoding video, full real-time playback of Multi-Ch synchronous decoding.
- Support Mobile iPhone,Android
- Support 1 HDMI ,1 VGA
- Support browsers : IE, Chrome, Firefox, Safari
- Support Back up by Network, USB burner, SATA burner

### Specification

Model	AN-AD9808T-M
Operating System	Embedded Linux
Sysytem resources	Simultaneous multi-channel real-time recording,Playback,Network,USB back up
Video Standard	PAL/NTSC (720P)
Video Compression	H.264(High Profile)
Video Input	8CH BNC
Video Output	1CH VGA, 1CH HDMI
Audio Compression	G.711A
Audio Input/Output	2CH / 1CH RCA
Display Quality	VGA,HDMI Support : 1920*1080,1280*720,1440*900,1280*1024,1024*768,800*600
Playback Quality	1080P/720P/D1/HD1/CIF
Encode/Decode Quality	8*720P
Record mode	Manual/Alarm/Motion detection/Timing
Network Interface	1 RJ-45 port (10/100Mbps)
PTZ Control	1*RS485, Support mutiple PTZ protocols
USB	2*USB 2.0
HDD	2 pcs * 4TB
Power Supply	12V/4A
Power Consumption	<15W (without HDD)
Temperature	10 °C ~ 55 °C
Humidity	10% ~ 90%
Pressure atmosphere	86Kpa ~ 106Kpa