

Cloud Alarm

Wi-Fi 01



hi-view[®]



WiFi Security Alarm System
Plug & Play Alarm System



WiFi Security Alarm System


hi-view®


Model	Cloud Alarm WiFi 01
Power Supply	DC 12V 500 mA
Battery	3.7V 600 mAh Li-ion x 1pc
Battery Life Recharge Cycle	300 times
Wifi	IEEE 802.11b/g/n
Standby Current	<27mA
Alarm Current	<180mA
Internal Siren	85 dB
Optional Accessories	10 Remote Controls, 50 Sensors
Radio Frequency	433.92 MHz
Housing Material	ABS Plastic
Control Panel Dimensions	125x150x30mm. (LxWxH)
Bracket Dimensions	87.5x81.5x12mm. (lxWxH)
Remote Control	
Power Supply	DC 3V (CR2025 lithium battery x 1pc)
Transmit Current	<7mA
Transmitting Distance	<80 m (open area/no interference)
Radio Frequency	433.92 MHz
Housing Material	ABS Plastic
Operating Condition	Temperature 0C~+55C Relative Humidity <80% (non-condensing)
Dimensions	53x31x11mm. (LxWxH)
Door/Window Sensor	
Power Supply	DC 3V (lithium battery x 2pcs)
Static Current	<5uA
Alarm Current	<9mA
Transmitting Distance	<80 m (open area/no interference)
Radio Frequency	433.92 MHz
Housing Material	ABS Plastic
Operating Condition	Temperature 0C~+55C Relative Humidity <80% (non-condensing)
Transmitter Dimensions	71x31.5x15mm. (LxWxH)
Magnet Dimensions	71x12.5x15mm. (LxWxH)
Pet Immune PIR Motion Sensor	
Power Supply	DC 3V (AA 1.5V LR6 battery x 2pcs)
Static Current	<25uA
Alarm Current	<13mA
Detection Scope	8m/110°
Transmitting Distance	<80 m (open area/no interference)
Radio Frequency	433.92 MHz
Housing Material	ABS Plastic
Operating Condition	Temperature 0C~ + 55C Relative Humidity <80% (non-condensing)
Detector Dimensions	100x59x43mm. (LxWxH)
Bracket Dimensions	52x30x26.5mm. (LxWxH)

